

**WaterMaster®**

# ADJUSTABLE NOZZLE

Adjustable from 25° to 360°



## Instructions for Adjustable Nozzle

53482 10'  
 53483 12'  
 53484 15'  
 53485 17'  
 53486 7'

### Nozzle Performance Data

Adjustable Nozzle	Radius Arc	Pressure psi	Flow GPM
53486 Brown 7' Adjustable Nozzle	90°	25	0.39
	180°	25	0.78
	360°	25	1.04
53482 Red 10' Adjustable Nozzle	90°	25	0.39
	180°	25	0.78
	360°	25	1.56
53483 Green 12' Adjustable Nozzle	90°	25	0.56
	180°	25	1.12
	360°	25	2.24
53484 Black 15' Adjustable Nozzle	90°	25	0.88
	180°	25	1.75
	360°	25	3.50
53485 Gray 17' Adjustable Nozzle	90°	25	1.13
	180°	25	2.25
	360°	25	4.50

GPM=Gallons per minute

psi=Pressure per square inch

Radius Arc=Spray Pattern




Figure A

- Turn water off.
- Remove old nozzle (if necessary).
- Place filter in stem with open end up (see Figure A).
- Screw nozzle on.



Figure B

- **Pattern Adjustment**  
Turn the top of the nozzle to the desired spray pattern from 25°-360° (see Figure B).

**Distance Adjustment**  
The radius adjustment screw in the center of the nozzle top reduces overspray up to 25%.




Figure C

- Adjust ratchet head stem to the desired starting point (see Figure C).

### Compatible with:

WaterMaster® 54080 & 54081, Orbit® 54400 series, Orbit® Hard Top®, Buckner®, Champion® 2000 series, Hunter® PS series, Irritrol Systems® Canopy®, Nelson® 6300 series, Weathermatic® LX series, and Rainbird® 1800 series.



- For use with male stem spring-loaded or shrub heads
- Fully adjustable arc from 25° to 360°
- Basket filters included

For outdoor use with cold water only.

Para uso exterior con agua fría.

For additional information  
 contact us at:  
 1.800.488.6156  
 www.orbitonline.com



Irrigation Products, Inc.  
 North Salt Lake, UT 84054

53482W-24 Rev A

Made in USA